Ficha Técnica Renault Fluence



Technical Specifications New Fluence 2015			
Versions / Engines	Dynamique / Dynamique CVT / Dynamique CVT Plus / Privilêge		
Architecture	5-passenger, 4-door, 3-box unibody		
Engine	2.0 16V Hi-Flex DOHC CVVT		
Drive type	Front		
Cubic capacity	1,997 cm³		
Bore x stroke	84.0 mm x 90.1 mm		
Compression ratio		10:01	
Maximum power (ABNT)	143 cv (ethanol) at 6,000 rpm / 140 cv (gas) at 6,000 rpm		
Maximum torque (ABNT)	20.3 kgfm (ethanol) at 3,750 rpm / 19.9 kgfm (gas) at 3,750 rpm		
Fuel injection type	Sequential multipoint fuel injection		
Wheels	R16 alloy wheels	R17 alloy wheels	
Tires	205/60 R16	205/55 R17	
Front suspension	MacPherson strut with lower wishbone, double-acting hydraulic shock absorbers, coil springs and stabilizer bar.		
Rear suspension	H-shaped deformable torsion beam, coil springs, integrated stabilizer bar and double-acting hydraulic shock absorbers		
Braking	ABS with Emergency Braking Assistance (EBA) and Electronic Braking Distribution (EBD), 280mm front ventilated discs and 260mm solid rear discs.		
Steering	Electric variable power steering		
Transmission type	6-speed manual	Continuously Variable X-Tronic CVT transmission, with optional 6-speed manual-sequential mode.	
Gear ratio	1st	Automatic mode: Minimum opening: 2.349 Maximum opening: 0.394 Sequential mode: 1st	
Fuel tank capacity	60 liters		
Trunk space	530 liters		
Payload	430 kg	413 kg	
Curb weight	1,369 kg	1,372 kg	
Wheelbase	2,700 mm		
Overall length	4,620 mm		
Overall height	1,470 mm		
Overall width (w/o door mirrors)	1,810 mm		
0-100kph	9.7 s (ethanol) / 9.9 s (gas)	9.9 s (ethanol) / 10.1 s (gas)	
Maximum speed	200 km/h	195 km/h	